

NuSeal Cleaning and Sealing Specifications

Product Description

NuSeal is an ultra-durable high gloss thermoplastic seal and finish for all types of stone and tile floors. NuSeal resists scuffs, scratches, heel marks and wear. NuSeal also has a higher slip resistance factor than most finishes so that it gives you an extra margin of error on marbles, terrazzo, granite and other hard floors.

1. Remove and sweep all debris off your newly installed Nurazzo flooring.
2. Hang and install plastic from the base up the wall approximately 24". The plastic will protect the wall from the slurry splash.
3. Place safety signs insight and in clear view of each entrance that leads into the area of work.
4. Stage the area with the following equipment: Heavy or weighted slow-speed machine 175 rpm to 325 rpm, wet-vac, mop bucket, mop, red or peach pad, ragas airmover.
5. Stage the area with the following materials: NuSeal acrylic sealer/finish, neutral cleaner.
6. Place the slow-speed machine in to position with proper pad beneath. Apply neutral cleaner (mixed with water) on to the surface. Begin to manually scrub surface with slow-speed machine in a checkered board fashion making a minimum of (2) passes or more. Once scrubbed vacuum water up and clean water rinse surface with a mop. (Follow the manufacturer suggested amounts for chemical and square footage).
7. Once step 6 is complete force dry the Nurazzo surface until dry. Apply the NuSeal with a micro-fiber pad. Apply a minimum of 3 thin coats of finish.
8. Hi-speed burnish or slow-speed burnish with a white pad or equivalent.



A **NU** DIMENSION IN TERRAZZO TILE

P.O. BOX 1208 DALTON, GA 30722

(P) 706-275-8000

(F) 706-275-8004

WWW.NURAZZO.COM

Application

All application tools must be clean and should not have been used for any other product. Prepare the floor first by stripping and neutralizing the surface making sure the floor is clean and dry before application. For best results, use a microfiber pad to apply the product. Apply a thin coat of NuSeal, allowing 30-45 minutes to dry before applying additional coats. Do not recoat until previous coat is completely dry. A minimum of 3 coats should be applied to achieve the overall high gloss appearance. Buffing will produce a beautiful shine.

Maintenance

Maintain NuSeal daily by dust mopping and damp mopping with a neutral cleaner. NuSeal can be spray buffed by using a low speed or high speed floor machine.

Coverage

Approximately 1500 sq ft per gallon.

Packaging

Available in 1 gallon pails or 5 gallon pails.

