



PO BOX 1208  
DALTON, GA 30722  
PH: (706) 275-8000 FAX: (706) 275-8004  
[www.nurazzo.com](http://www.nurazzo.com)

## **Nurazzo Impregnator/Nurazzo Impregnator Plus**

### **Floor Preparation**

Floor areas must be clean and double rinsed to remove all traces of acid wash or other cleaning solutions. Allow floor surfaces to dry before applying impregnator. Floor temperature should be 60° F and stable. If area has been previously treated with any sealer, a test must be made for compatibility.

### **Application**

Nurazzo Impregnator or Nurazzo Impregnator Plus should be applied with a lambs wool applicator to a clean dry surface using a thin coat, avoid puddling. Allow to dry, then remove any excess with a clean dry cloth. Then polish to remove any residue using a nylon polishing white pad under a (175-300) rpm buffer. For maximum protection apply a second coat in 24 hours and repeat the process. The second application is not required. These two products are both an impregnation water and oil resistant treatment for terrazzo

### **Coverage**

Approximate 1200 sq ft per gallon

### **Packaging**

Available in 1 gallon pails or 5 gallon pails.

### **Maintenance Instructions**

Maintaining the floor is the key to longevity of the appearance of the floor. Keeping the floor clean of abrasive grit is key. Dry-mop everyday to remove abrasives off the floor. If the floor is prone to getting wet, then the floor should be dried as soon as possible to keep debris from sticking to the floor.

Depending on traffic and maintenance these two products will give you up to a year of protection. The appearance of the floor is the best indicator if the maintenance intervals are keeping the floor in good condition. If the appearance starts to dull both of these products can be reapplied and buffed as during the first application. Nurazzo tiles do not require a wax application. One may be applied if desired. Wax or any other finishes applied must be removed before reapplying Nurazzo Impregnator.