



Sunbrite

Application & Maintenance Instructions

Product Description

Sunbrite is an ultra-durable high gloss thermoplastic seal and finish for all types of stone and tile floors. Sunbrite resists scuffs, scratches, heel marks and wear. Sunbrite also has a higher slip resistance factor than most finishes so that it give you an extra margin of error on marbles, terrazzo, granite and other hard floors.

Floor Preparation

Floor areas must be clean and double rinsed to remove all traces of acid wash or other cleaning solutions. Allow floor surfaces to dry before applying sealer. If area has been previously treated with any sealer, a test must be made for compatibility. A damp surface will require more time for sealer to cure.

Application

All application tools must be clean and should not have been used for any other product. Prepare the floor first by stripping and neutralizing the surface making sure the floor is clean and dry before application. For best results, use a white, nylon finish mop to apply the product. Apply a thin coat of Sunbrite, allowing 30-45 minutes to dry before applying additional coats. Do not recoat until previous coat is completely dry. A minimum of 3 should be applied to achieve the overall high gloss appearance. Buffing will produce a great shine.

Maintenance

Maintain Sunbrite daily by dust mopping and damp mopping with a neutral cleaner. Sunbrite can be spray buffed by using a low speed or high speed floor machine.

Coverage

Approximate 1500 sq ft per gallon

Packaging

Available in 1 gallon pails or 5 gallon pails.